

75S8U Specification

Model Name:75S8U

Platform Model: M-MT9632T8E-DVB

Brand:MECER

Figure



1.Panel spec

Size	75"diagonal
Backlight	DLED direct Type
Maximum resolution	3840×2160
LCM Center Luminance of White	Min.:330cd/m2;Typ.380cd/m2
Contrast ratio (Typ)	1200:1
Response time(Typ)	8ms
Display scale	16:09
Viewing angle(CR>10)	Min(H:178°V:178°)
Display Colors	1.07 B
Color Gamut(NTSC)	≥NTSC 62%

2.Hardware Information

CPU Frame	ARM Cortex-A53/1.5GHz/Quad core
GPU	G52MP2/Dual core
RAM(DDR3)	1.5GB
ROM(Flash)	8GB (16GB optional)
Audio power(Output)	8W+8W
WIFI(Type)	2T2R
HDMI 1.4 (HDCP 1.4)	-
HDMI 2.0 (HDCP 2.2)	3
USB 2.0	2
USB 3.0	-
VGA	-
AV In	1
YPbPr In	-
CI	1
PC Audio	-
RJ-45	1

Earphone	-
Audio In	-
Audio Out	1
Video Out	-
SPDIF Out	1(optical)
3.Software Function	
Channel list	YES
Channel edit	YES
Picture freezing	NO
MTS/NICAM	MTS
Sleep time setting	YES
Teletext	YES
PVR	YES
EPG	YES
V CHIP/Parental Guidance	Parental Guidance
CC(Closed caption)	NO
AD(Audio description)	YES
TTS(Text to Speech)	NO
CI+	YES
DOLBY	YES
HDMI-ARC	HDMI-1
HDMI-CEC	YES
HDMI-MHL	NO
Operation system	Android 9.0
OTA	YES
4.Structure Information	
Base model name	BCD2-75 Gemini shaped metal stand
Size (without stand) L×W×H	1674x75x960mm
Size (with stand) L×W×H	1674x353x1024mm
Size (carton) L×W×H	1824x187x1085mm
Net Weight (without stand)	28.2kg
Net Weight (with stand)	28.7kg
Gross Weight (without stand)	36.6kg
Gross Weight (with stand)	37.1kg
Size (Wall hanging)	600x300mm
5.Power Management&Safety&Certificate	
Power input	100-240VAc
Fire rating	UL94-HB75

Standby power	≤0.5W
Rated power	300W
Working condition	Temperature:5°C~40°C, Humidity:10%~85%, Atmosphere:86KPa~106KPa
Storage condition	Temperature:-20°C~55°C, Humidity:5%~95%, Atmosphere:86kPa~106kPa

6.Accessory

Stand(Optional)	1PCS
Remote control	1PCS
Instruction	1PCS
Warranty card(Optional)	1PCS
Battery(Optional)	2PCS

Remark 1: The panel parameters will be somewhat different between different panel, please refer to the corresponding panel.